

## Description

This double-sided tape consists of a rayon carrier layered on both sides with a rubber adhesive. The aging resistant adhesive is lined with a double-sided silicone paper.

## Carrier

Rayon

## Liner

Silicone coated paper on both sides, 80 g/m<sup>2</sup>, brown

## Adhesive

Rubber

## Area of use

This especially rip-resistant, double sided tape is very flexible and is suitable for bases such as metal and wood. Limited plasticiser resistance. Not appropriate for artificial stone floors or marble.

## Technical data

<b>Thickness*</b> (adhesive + carrier)	230 micron	
<b>Temperature resistance***</b>	-20°C to +70°C	
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	17 N/25mm
	after 20 min	19 N/25mm
	after 24 h	21 N/25mm
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 5 h	at 23°C
	3 min	at 70°C
<b>Shelf life**</b>	1 year	
<b>Application temperature</b>	> +15°C	

\* average      \*\* in original packaging, at 20°C and 50% relative humidity

\*\*\* 1h, normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.