

Cast, fluorescent sheets

Product

The fluorescent PLEXIGLAS® sheet grades incorporate the latest generation of high-quality fluorescent colorants and constitute a natural, harmonious range of hues. This impressive play of colors is a source of inspiration for designers and creative minds, and irresistibly attracts the viewer's attention.

Properties

Besides the general properties of fluorescent PLEXIGLAS® like

- Excellent light transmission and brilliance
- Outstanding weather resistance
- 100% recycling ability
- Easy to fabricate
- High surface hardness
- Light weight – half the weight of glass
- 11 times more break resistant than glass

fluorescent PLEXIGLAS® possesses the following properties:

- Fluorescent coloring: UV and blue light is converted into glowing colors, for example, into green. No electrical power is needed for the sheet to glow.
- The use of high-quality fluorescent colorants makes for outstanding and enduring luminosity and superior colorfastness.
- Broad spectrum of blue, green, and red, orange, and yellow tones.

- Available in transparent (clear) or translucent grades.
- Also available on request with satin surfaces.
- The light-guiding properties of the transparent grades cause edges and routed areas to glow in ambient light.
- The luminous surfaces of the translucent grades create interesting effects.
- Large processing window for cast PLEXIGLAS®

Applications

People have always been fascinated by fluorescent colors because of their strong impact. That is why they are always used in places designed to arrest the eye, for example in

- Product displays
- Shopfitting
- Interior design
- Furniture
- Exhibition booth

Processing

Fluorescent PLEXIGLAS® can be machined with the same parameters and equipment as standard PLEXIGLAS®. The following fabricating guidelines are available:

- Machining of PLEXIGLAS® (No. 311-1)
- Forming of PLEXIGLAS® (No. 311-2)
- Joining of PLEXIGLAS® (No. 311-3)

- Surface treatment of PLEXIGLAS® (No. 311-4)
- Fabricating tips of PLEXIGLAS® solid sheets (No. 311-5)

Product range

Fluorescent PLEXIGLAS® is available in the size 3050 x 2030 mm with a thickness between 3 and 20 mm.

For details please refer to the PLEXIGLAS® sales handbook.

Technical data

For typical data of fluorescent PLEXIGLAS® please see the Technical Information of PLEXIGLAS® GS/XT (211-1).

® = registered trademark PLEXIGLAS is a registered trademark of Evonik Röhm GmbH, Darmstadt, Germany.
Certified to DIN EN ISO 9001 (Quality) and DIN EN ISO 14001 (Environment)

Evonik is a worldwide manufacturer of PMMA products sold under the PLEXIGLAS® trademark on the European, Asian, African and Australian continents and under the ACRYLITE® trademark in the Americas.

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Performance Materials GmbH

Acrylic Polymers

Kirschenallee, 64293 Darmstadt, Germany

info@plexiglas.net www.plexiglas.net www.evonik.com

Ref. No. 222-20 July 2015